



Main

Range of product	Unica
Product or component type	USB charger
Device presentation	Mechanism with plastic fixing frame
Colour tint	Graphite
Type of packing	Flow-pack
Quantity per set	Set of 1
Sale per indivisible quantity	1

Complementary

Device mounting	Flush
Connector type	USB 2.0
[Ue] rated operational voltage	100...240 V AC 50/60 Hz
Power consumption	< 0.1 W
Input power	7.5 W
Output voltage	5 V DC 1 A
Material	Internal cover : PC (polycarbonate) GF10 FR Casing : PC (polycarbonate) GF10 FR Centre plate : ABS
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1.5...2.5 mm ² stranded 1.5...2.5 mm ² flexible 1.5...2.5 mm ² rigid
Wire stripping length	8 mm
Product compatibility	All devices fulfilling the EN 62684 standard
Fixing mode	By claws By screws
Height	45 mm
Width	22.5 mm
Depth	42 mm
Embedding depth	30.8 mm
Product weight	0.03 kg

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	2004/108/EC EN 60950-1 2006/95/EC EN 62684 EU directive 2002/95/EC WEEE directive 2002/96/EC ETSI EN 301 489-4
Electrical insulation class	Class II
Environmental characteristic	REACH Regulation (EC) No 1907/2006

IK degree of protection	IK04
IP degree of protection	IP20
